

UDM_{MC}



EtherCAT[®] Dual & Quad Axis Drive Module

- Universal dual/quad motor Drive Modules for EtherCAT networks
- 12Vdc to 80Vdc, up to 20A continuous and 40A peak current
- Outstanding servo performance
20kHz sampling rate
Advanced algorithms including ServoBoost[™] (optional)
Gantry MIMO Control
Dual feedback
- Digital control for easy setup and diagnostics
- Supporting any of the following type of motors by software settings only:
2, 3 phase AC Servo / DC brushless with sinusoidal commutation, DC Brush, voice coils, Closed and open loop step motors
- Feedback
4 digital incremental encoders
4 absolute encoders (optional)
- Digital I/O (all can be used as general purpose I/O)
Inputs: 4 Registration MARK (High Speed Position Capture)
Outputs: 1 PEG (Position Event Generator), 4 motor brake (24V, 0.5A)
- Safe Torque Off (optional)
- Four axis units can be ordered also with mix current levels:
2 x 5A & 2 x 10A
2 x 5A & 2 x 20A
2 x 10A & 2 x 20A
- Compact footprint: 152 x 138 x 48 mm³

The UDM_{MC} is a line of compact EtherCAT modules of two and four universal drives with rating of 12 to 80Vdc and 2.5A (5A peak) to 20A (40A peak) per drive. Each drive is programmable to control a 3 & 2 phase servo motor, a DC brush motor, a voice coil motor and a 2 & 3 phase step motor.

The UDM_{MC} addresses the needs of demanding multi-axis motion applications with limited space, such as wafer-handling robots, wire bonders, die bonders, electronics packaging, small manipulators, and table-top motion stages. With the optional powerful ServoBoost[™] algorithm (ordered with the controller), demanding positioning systems can achieve ultimate performance levels, such as speeds of meters per seconds and Nanometers of jitter, minimal settling time, and uncompromising system robustness with minimal sensitivity to disturbances and changes. Optional Safe Torque Off (STO) cuts the power to the motor without removal of the power source for applications that are required to comply with SIL-3 and PLe safety levels. The UDM_{MC} is a slave that runs under any ACS' EtherCAT masters. The 4-axis UDM_{MC} can be ordered with mixed current specifications. See Ordering Options. A comprehensive set of software support tools are provided for configuration, setup, tuning and diagnostics.

CE, UL Pending

EtherCAT[®] is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany

Contact us: sales@acsmotioncontrol.com | www.acsmotioncontrol.com

ACS
MOTION CONTROL

Specifications

Per Drive	2.5A	5A	10A	20A
Continuous/peak current Sine amplitude [A]	2.5/5	5/10	10/20	20/40
Continuous current RMS [A]	1.75/3.5	3.5/7	7/14	14/28
Heat dissipation [W]	1	1.2	3	8
Maximum cont./peak output power @ 80Vdc [W]	155/310	313/625	625/1250	1250/2500
Maximum cont Input current [A]	2	4	8	16
Peak current time [sec]	1			
Minimum load inductance @80Vdc [mH]. Can be derated linearly for lower voltages	0.05			

Per module	
Maximum cont input current per module [A]	40
Maximum motor voltage [Vdc]	(Vin motor) x 92%

Drives

Type: digital current control with field oriented control and space vector modulation
Current ripple frequency: 40 kHz
Current loop sampling rate: 20 kHz
Programmable Current loop bandwidth: up to 5 kHz
Commutation type: sinusoidal. Initiation with and without hall sensors
Switching method: advanced unipolar PWM
Protection: Over & under voltage, Phase to phase and phase to ground short, Over current, Over temperature

Supply

The drive must be supplied by two power sources A motor supply and a 24Vdc control & logic supply. During emergency conditions there is no need to remove the 24Vdc control supply.

Motor Supply

Range: 12Vdc to 80Vdc
Current rating should be calculated based on actual load.
External shunt power resistor, activated at 83V, should be added in parallel to motor supply, which must not exceed 85V under any operating conditions.

Control Supply

Control supply input voltage: 24Vdc \pm 20%
Maximum input power:
Without motor brakes: 19W (0.8A @ 24Vdc)
With 4 motor brakes: 67W (2.8A @ 24Vdc)

Motor Type

DC Brush, Voice coil
2 & 3 phase AC synchronous (DC Brushless servo) motor

2,3 & 5 phase step motor.

Always using high resolution microstepping.

Feedback

Types: incremental digital encoders, optional: absolute encoders

Incremental Digital Encoder: Four, one per axis. A&B,I and Clk/Dir, Type: Differential RS-422 or single-ended

Max. rate: RS-422 - 50M quad counts/sec, Single-ended: 2M quad counts/sec.

Protection: Encoder error, not connected

Absolute encoders (optional): Up to four.

EnDat 2.1(Digital)/2.2, Panasonic, Smart-Abs, and BiSS-C

Hall inputs:

Four, a set of three per axis. Type: single-ended, 5V, source, opto-isolated

Input current: <7mA

5V feedback supply

Feedback devices are fed by a 5V \pm 5% supply. Total current provided by the internal supply: 0.5A. If more current is needed, an external supply should be used, using the dedicated connector

Digital I/O

Axis' Limit inputs: Eight, Two per axis.

Type: Single-ended, 5/24V \pm 20%, opto isolated, sink/source. 14mA per input

Unused limit inputs can be used as general purpose inputs

STO: Two inputs. Current per input <50mA

All drives are disabled within 50mS to 200mS

Ordering Options

Ordering options	Field	Example	Values
Number of axes	1	2	2,4
Continuous Current (Peak is double)	2	B	2x5A (A), 2x10A (B), 2x20A (C), 4x2.5A (J), 4x5A (D), 4x10A (E), 4x20A (F), 2x5A & 2x10A (G), 2x5A & 2x20A (H), 2x10A & 2x20A (I)
Total number of digital incremental encoders	3	4	2, 4. For 4-axis unit select 4
Absolute encoders type	4	N	None, Digital EnDat 2.2(E), Smart Abs(S), Panasonic(P), BiSS-C (B)
Number of Absolute encoders interface	5	0	0,1,2,3,4
STO	6	Y	Yes (Y), No (N)
I/O configurations	7	N	(N) Inputs & limits: 24V,SOURCE (PNP), Outputs : 24V,SOURCE (PNP). (S) Inputs & limits: 24V,SINK (NPN). Outputs: 24V,SOURCE (PNP). (A) Inputs & limits: 5V/SOURCE (PNP). Outputs: 24V/SOURCE (PNP). (B) Inputs & limits: 5V/SINK (NPN). Outputs: 24V/SOURCE (PNP)

Example: UDMmc2B4N0YN

Field		1	2	3	4	5	6	7
PN	UDM _{MC}	2	B	4	N	0	Y	N

Registration MARK (High Speed Position

Capture) Inputs: Four, 24V \pm 20%, opto-isolated, two terminals. Can be configured as 'sink' or 'source'. Input current <14mA. Can be used as general purpose inputs.

Motor Brake Outputs: Four, opto-isolated, source, 24V \pm 20%, 0.5A. Can be used as general purpose outputs.

Position Event Generator (PEG): One, RS422.

Can be used as general purpose output. Pulse width 26nSec to 1.75mSec. Maximum rate: 10MHz

Drive Protection

- Over & under Voltage
- Short circuit: Phase-to-phase, Short to ground
- Over current
- Over temperature

Environment

Operation: 0 to + 50°C

Storage and transportation: -25 to +60°C

Humidity (operating range): 5% to 90% non-condensing

Communication

Two EtherCAT ports, In and Out, RJ45 connector

Dimensions

152x138x48 mm³

Weight

1,000 [gram]

Accessories

UDMmc-ACC1: Mating connectors kit for drives, encoders and I/Os

STO-ACC1: Cable for STO with mating connector

For the latest updates visit our website at www.acsmotioncontrol.com

ACS
MOTION CONTROL